

LED FULL CUTOFF WALL PACK LIGHT



E2-RWP-25WA1: 360° Adjustable module



Technical Requirements Version: 4.1

Color: Black Weight: 4.07 lbs

Project Name:

Catalogue Number:

Fixture Schedule:

Comments:

Specifications

Light Output	3000-3300 LM	Frequency	50-60 Hz
Efficacy	≤ 132 LPW	THD	< 20%
Wattage	25 W	L70 Lifespan	50,000 hours
Color Accuracy (CRI)	> 70	IP Rating	IP54
Kelvin (CCT)	4000-5700 K	Beam Angle	type 3
Power Factor	> 0.90	Dimming Compatible	No
Working Environment	-4.0° F~113° F	Mercury Content	No Hg
Input Voltage	100-277VAC	Lens	Polycarbonate

Product Description

E2 Lighting's Full-Cutoff LED Wall Packs are available in 25-, 40-, 60- and 80-watts. These wall packs were designed and engineered as maintenance free, energy-efficient alternatives to traditional fluorescent, high/low pressure sodium, metal halide, induction and other types of lighting fixtures. The wall packs provide highly effective delivered lumens for outdoor illumination hotels at garages, commercial buildings, public spaces, schools and universities and hospitals. All Full-Cutoff LED Wall Packs are available in 4000-5700K correlated color temperature (CCT) and maximize brightness. In addition to diminishing energy costs, the fixtures virtually eliminate maintenance expenses with an L70 lifetime of 50,000 hours. UL classified/recognized, UL listed, DLC listed and RoHs compliant.

Product Features

- UL cUL certificate
- IP65 Internal driver
- Input voltage 100-277VAC
- No UV or IR in the beam
- Easy turnkey installation and operation
- Instant start, No humming
- Green and eco-friendly with no mercury
- Long life LEDs lasting up to 50,000 hours
- DLC and UL wet location listed

Applications

- Primary use: Outdoor Full-Cutoff Wall-Mounted Area Luminaires
- Entrance, Courtyard, Industrial, Outdoor Landscaping, Building, Hotel and any Wall Lighting areas and/or environments

Available Options

- Optional color temperatures 4,000-5,700 K

Cautions

- Installation by a licensed electrician only.
- Product failure caused by misuse, modification or power surges are not covered under warranty.
- Actual product performance may differ as a result of end-user environment and application.
- Input voltage may vary depending on photocell configuration.

Warranty

E2 warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. Please see our full warranty terms located at www.e2lightingusa.com.

Technical Support

Need help? Please contact our technical support team for assistance at (415) 670-9362.

Dimensions

Dimensions conversion:
9.13 (232) x 5.39 (137) x 5.19in (132mm)

Ordering Matrix

Model	Watts	Finish	CRI	Voltage	Luminous Flux	Efficacy	Net Weight
E2-RWP-25WA1 4000K	25	Black	73.5	100-277VAC	3300	126.99	4.07 lbs
E2-RWP-25WA1 5000K	25	Black	73.5	100-277VAC	3300	129.66	4.07 lbs
E2-RWP-25WA1 5700K	25	Black	73.0	100-277VAC	3400	132.19	4.07 lbs

Model # E2-RWP-25WA1 5000K



Manufacturer: E2 Lighting International Inc.
Brand: E2 Lighting International Inc.
Technical Requirements Version:
Date Qualified: 02/03/2017
Product ID: PZY43U6V

Categorization

Main: Outdoor Luminaires
General Application: Low Output
Primary Use: Architectural Flood and Spot Luminaires

Classification: Premium
Is Parent Product: No
DLC Family Code: VAVWCX
Dimming Status: NotDimmable
Listing Status: Listed

Reported Data

Family Data

Light Output: 3280.3 lm
Wattage: 25.3 W
Efficacy: 129.66 lm/W
Power Factor: 0.91
CCT: 5000 K
CRI: 73.5
Total Harmonic Distortion: 14.07 %