



**NEW**

# NON CUT-OFF WALL PACK CCT and Wattage Tunable

## W/ Emergency Battery Back Up & Photocell

**Model:** WP01-80[L,M]-[MC,PC,PSC,SC,C]- 3CCT


Photocell


**Dimension:**


10W Emergency Battery for 90 mins

**PRODUCT DESCRIPTION:**

E2 LIGHTING'S Non Cut-Off Wall Pack is a highly efficient, multi-function fixture that provides a long-lasting and energy saving lighting solution. This fixture is equipped with Internal CCT color temperature and wattage tunable switch. The rugged housing offers advanced thermal management and protection against outdoor environments without compromising aesthetics.

**FEATURES AND STANDARDS:**

- ETL/cETL/DLC premium certificate.
- Pre-wired 10W Emergency Battery with Indicator Push button
- 1250lm in battery mode for 90 mins
- Wet location rated IP65.
- Durable die-cast aluminum housing.
- Wattage and CCT tunable.
- UV-resistant polycarbonate refractor lens.
- Photocell
- Option : Motion sensor

**APPLICATION:**

Outdoor wall-mount applications: building facade, commercial, industrial, retail, hospitality buildings that demand long service life and low maintenance.

**TESTED DATA:**

- Input Power - 30/40/60/80W Tunable
- Lumen - 3900/5200/7800/10400lm
- Efficacy - 125LM/W ( $\pm 10\%$ )
- Input Voltage - 120-277VAC
- Color Temperature - 3000K-4000K-5000K Tunable
- THD -  $< 20\%$
- Dimmable - 0-10V
- LED Brand - Lumileds
- LED Type - 3030
- LED QTY - 48/72/96 pcs
- Operating Temperature - 86°F to 113°F ( $-30^{\circ}\text{C}$  to  $+45^{\circ}\text{C}$ )
- Operating Humidity - RH $< 90\%$
- Color Rendering Index - Ra $> 70$
- IP Rating - IP65
- Certification - cETL/ETL/DLC Premium
- Housing - Die-cast Aluminum
- Life Time -  $> 50,000$ Hrs
- Warranty - 5 Years