



E2 Lighting International Inc.

Project Name: \_\_\_\_\_ Catalog Number: \_\_\_\_\_

Notes: \_\_\_\_\_ Fixture schedule: \_\_\_\_\_

## Fire Rated LED Panel Light

E2-DL-SLIM-4inch-9W-27/30/35/40/50K-F  
E2-DL-SLIM-6inch-12W-27/30/35/40/50K-F



## Product Description:

Each LED panel is built with an Fireproof Cotton that is activated at temperature above 190 °C and unidirectional expansion the 5 times soon, to prevent fire and smoke spread to other parts of the building, and ultimately slow the spread of fire.


## Features

- 2 Hour Fire Rated without Additional Housing or Hardware
- 0-10V Dimming
- Plenum Rated Cable for Commercial Installations
- Type IC & Air-Tight Rated - No Housing Required
- Input Voltage 120-277V
- Driver Inside Connection Box – No Junction Box Needed
- 5 CCT User Selectable Light Colors
- CRI 90+ for True Color Rendering

Materials--flame retardant material  
Metal Fireproof Paint  
Fireproof Cotton  
Fully Seale Iron Back Cover  
Metal Cilps  
Metal Wire Connector



## Physical Dimensions



Phone: 469-638-3592 Fax: 213-477-2257 Web: [www.e2lightingusa.com](http://www.e2lightingusa.com) E-mail: [sales@e2lightingusa.com](mailto:sales@e2lightingusa.com)




Specifications

Item No.		Diameters	Cut Out	CCT	Input Voltage	CRI	Carton Size	Dimmable
E2-DL-SLIM-4inch-9W	9W	OD 125mm H 24mm	105mm	2700K- 5000K	100-277V	≥ 90	54*28*34.5cm	0-10V
E2-DL-SLIM-6inch-12W	12W	OD 175mm H 24mm	155mm				155mm 39*39*32cm	

Product Structre




Photometry



Installation

Fig.1



or




Fig.2




Fig.3

