

10 SERIES - LED Tunable Commercial Down Light

The 10 SERIES - LED Tunable Commercial Down Light Up to 120 lm/W, IP54 Wet Location, Selectable 5X CCT (2700K/3000K/3500K/4000K/5000K) and 5X Wattages 0-10V Dimmable, Premium Indoor Luminaire.

Premium Features

Lumen Output	600 to 3960 lumens
Efficacy	Up to 120 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select 27K-30K-35K-40K-50K
IP Rating	IP54 Wet Location
Size	8-in
Warranty	5 Years

Applications

Premium indoor luminaire for recessed mounting in ceiling spaces. Suitable for general indoor, lobbies, offices, meeting rooms, restrooms, hallways, hospitals, airports, hotels, restaurants and shopping centers.

Construction

Manufactured for durability using airtight aluminum sheet housing with satin coating to resist corrosion, discoloration, and scratching. IP54 Wet Location rated for protection against dust and splashing water: IEC 60529. Deep recessed lens to minimize ambient glare.

Electrical

Input voltage 120-277V models with 0-10V Continuous Dimming. Includes 5X-CCT and 5X-Wattage Tuning Switches. Operating temperatures -4°F to 104°F (-20°C to 40°C).

Mounting

Quick installation spring-bars for installations without housing. 1.5 Foot integrated whip for easy access to the junction box.

Optics

Anti-UV Frosted Polycarbonate Lens.

Listings

ETL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. ENERGY STAR listed to qualify for energy-efficient LED lighting rebates.

Warranty

5 yr /50K hrs.


Project:
Date:
Catalog No:
Prepared By:

4-in, 6-in, 8-in, and 10-in Models



5X CCT & 5X Wattage Tunable

Tuning Switches on Housing



Specifications

Energy Data

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: Select (16W/22W/26W/30W/35W)

Power Factor: >0.9

Total Harmonic Distortion (THD): <20%

Operating Temperature: -4°F to 104°F (-20°C to 40°C)

Lighting Data

Lumens: Select 1600, 2200, 2600, 3120, 3960

Lumens Per Watt: Up to 120 lm/W

Color Correlated Temperature (CCT): Select (27K-30K-35K-40K-50K)

Dimmable: 0-10V

Color Rendering Index (CRI): >80

L70: 50000 hours

Ordering Information

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Beam Angle	Dimming	Color	Dimensions	Weight
E2-DL-254-8-35W-OAC5-	8-in	(16W 22W 22W 35W)	120-277V	0.10A@120V, 0.04A@277V 0.13A@120V, 0.06A@277V 0.18A@120V, 0.08A@277V	1200 1600 3500	100 lm/W	2700K (3000K, 3500K 4000K, 5000K)	90°	0-10V	White	Luminaire ø 10.31"C x 4.88"H Cutout Min. ø 8.00"C, Max. ø 9.50"C	1.34 lbs

Shipping Information

Model Wattage	Unit Weight	Shipping Dimensions	Shipping Weight	Quantity /Box
4-in	0.66 lbs	21.22"L x 13.23"W x 20.20"D	22.66 lbs	24
6-in	1.12 lbs	18.50"L x 17.87"W x 17.71"D	19.79 lbs	12
8-in	1.34 lbs	22.83"L x 21.73"W x 19.29"D	22.11 lbs	12
10-in	1.65 lbs	24.72"L x 12.99"W x 21.18"D	15.90 lbs	6

Physical Dimensions

4 in Models ø 5.94"C x 3.63"H

6 in Models ø 8.31"C x 4.38"H

8 in Models ø 10.31"C x 4.88"H

10 in Models ø 11.56"C x 5.50"H

