

E2-WP10

2020 FULL CUT-OFF WALL PACK

NEW
30W 40W 60W 80W
with 2-in-1 Motion Sensor / Photocell & Emergency Battery Backup

Good heat dissipation, light weight, cost-effective and low transportation cost.


UV-resistant polycarbonate refractor lens.

Emergency Battery Backup test button & indicator light.

EVA foam for good sealing

Plug & Play sensor with microwave and daylight harvesting function, 2-in-1 sensor.

Built in level


4W battery - 30W & 40W fixtures

10W battery - 60W & 80W fixtures


PRODUCT DESCRIPTION:

E2 LIGHTING'S Full Cut-Off Wall Pack is a highly efficient, multi-function fixture that provides a long lasting and energy saving lighting solution. This fixture comes equipped with a plug & play 2-in-1 microwave motion sensor and daylight harvesting photocell; along with an integrated emergency backup battery that delivers at least 90 minutes of emergency light in the event of power loss. The rugged housing offers advanced thermal management and protection against outdoor environments without compromising aesthetics.

FEATURES AND STANDARDS:

- ETL/cETL/DLC Premium certificates.
- Easy installation.
- IP65 Wet location rated.
- Durable die-cast aluminum housing.
- Photocell and motion sensor options.
- UV-resistant polycarbonate refractor lens.
- 4W emergency power on 30/40W models and 10W emergency power on 60/80W models. Operating time 1.5 hours.
- Type III distribution optics standard. Other optics available on request.

APPLICATIONS:

Outdoor wall-mount applications: building facade, commercial, industrial, retail, hospitality buildings that demand long service life and low maintenance.



TESTED DATA:

- Input Power - 30/40/60/80W
- Lumen Output - 3900,5200,7800,10400lm
- Efficacy - 130lm/W (±10%)
- Input Voltage - 120-277VAC
- Color Temperature - 5000K
- THD - <20%
- Dimmable - 0-10V
- LED Brand - Lumileds
- LED Type - 3030
- LED QTY - 48,48,72,96 pcs
- Viewing Angle - Type III
- Operating Temperature - 86°F to 113°F (-30°C to +45°C)
- Operating Humidity - RH<90%
- Color Rendering Index - Ra>70
- IP Rating - IP65
- Certification - cETL/ETL/DLC Premium
- Housing - Die-cast Aluminum
- Life Time - >50,000Hrs
- Warranty - 5 Years





Model Number	Wattage	Color	Certifications	Dimming	Voltage	Lumens	Working Hours	CRI
E2-WP10-30W-50-E-M/P	30W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	3900lm	50,000hrs	Ra>70
E2-WP10-40W-50-E-M/P	40W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	5200lm	50,000hrs	Ra>70
E2-WP10-60W-50-E-M/P	60W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	7800lm	50,000hrs	Ra>70
E2-WP10-80W-50-E-M/P	80W	5000K	cETL/ETL/DLC Premium	0-10V	120-277Vac	10400lm	50,000hrs	Ra>70

DIMENSIONS



30/40W



60/80W

